

HDR optical module



Overview

Absolute maximum ratings are those beyond which damage to the device may occur. Prolonged operation between the operational specifications and absolute maximum ratings is not intended and may cause permanent device degradation. Absolute maximum ratings are those beyond which damage to the device may occur. Prolonged operation between the operational specifications and absolute maximum ratings is not intended and may cause permanent device degradation. dBm This table shows the environmental specifications for the product. Supply voltage (Vcc) Power consumption (each end, retiming Min) The transceiver can be damaged by exposure to current surges and over voltage events. Take care to restrict exposure to the conditions defined in Absolute Maximum Ratings. Observe normal handling precautions for electrostatic discharge-sensitive devices. The transceiver is shipped with dust caps on both the electrical and the optical port. The cap. Near-end ESMW (Eye Symmetry Mask Width) Near-end output eye height.

Article Content

NVIDIA/Mellanox Compatible 400G OSFP 2xSR4 850nm 50m Dual

NADDOD OSFP-400G-2xSR4H is an Eight Channel, Parallel, Pluggable, Fiber-Optic OSFP for 400Gigabit Ethernet applications. This InfiniBand HDR transceiver is a high performance module for

200Gb/s QSFP56 HDR SR4 850nm 100m MMF Optical

This module incorporates integrated circuit technology in order to provide high performance. The transceiver operates over 4-lane parallel multi-mode fiber (MMF), using a nominal

HDR QSFP56 MMF Transceiver

HDR QSFP56 MMF Transceiver MMA1T00-HS Mellanox® MMA1T00-HS transceiver is a 4-channel, pluggable, QSFP56, optical transceiver designed for use in 200Gb/s InfiniBand applications. This

12G-SDI Video SFP 1310nm 10km Transceiver for

12G-SDI UHD Video SFP Fiber Optical Transceiver Module for 12G/6G/3G/HD/SD-SDI (SMF, 1310nm, 10km, LC, DOM, MSA) Optcore's OHP12G-3110DCR is a

MMA1T00-HS HDR QSFP56 MMF Transceiver Product

The NVIDIA ® MMA1T00 transceiver is a 4-channel, pluggable, QSFP56 optical transceiver, designed for use in 200Gb/s HDR InfiniBand

NVIDIA/Mellanox® MMA1T00-HS InfiniBand HDR

NVIDIA/Mellanox MMA1T00-HS (980-9I17S-00HS00) Compatible 200G SR4 QSFP56 4x50G PAM4 850nm 100m MMF DOM MPO-12/UPC InfiniBand HDR

Mellanox MMA1T00-HS Compatible 200G QSFP56 SR4

They work perfectly with all of our existing QSFP56 and Infiniband HDR-enabled

200G QSFP56-SR4 850nm 100m MMF InfiniBand HDR Optical Transceiver Module

TARLUZ 200G QSFP56 SR4 optic transceiver is designed for 200G Ethernet, it is able to transmit up to 70m via OM3 fiber, and 100m via OM4 fiber. The module with 4x channels, and each channel

What makes e-con's 4K HDR camera module a perfect

Modern microscopes use cameras to capture minute details of test samples - thereby improving the accuracy and speed of diagnosis. In this article,

Digital Video Transceivers | 12G/6G/3G/HD/SD-SDI Optical Modules ...

Digital Video Transceivers are optical modules designed for high-performance video transmission across broadcast and professional AV systems. Supporting 12G, 6G, 3G, HD, and SD-SDI standards, these

Introducing 200G HDR InfiniBand Solutions

Introducing 200G HDR InfiniBand Solutions White Paper ConnectX-6 also offers a crucial innovation to data center security by providing block-level encryption. Data in transit undergoes encryption and

Optifiber Pro HDR Module

Optifiber Pro HDR Module Features: Multiple wavelengths (850, 1300, 1310, 1490, 1550 and 1625 nm) support LAN, datacenters, PON, FTTx and outside plant

HDMI-OPTN-TX200AU2K | HDMI SDVoE Optical Extender

Fiber Optical Extender for HDMI 2.0 Signals The HDMI-OPTN-TX200AU2K and HDMI-OPTN-RX100AU2K transmitter and receiver devices are

NVIDIA/Mellanox MMA1T00-HS Compatible 200GBASE-SR4

The NVIDIA/Mellanox MMA1T00-HS Compatible QSFP56 InfiniBand HDR Optical Transceiver is an InfiniBand 200Gb/s Single-port QSFP56, SR4 multimode parallel transceiver using a single, 4

200G QSFP56 HDR Optical Module Transceiver for InfiniBand

200G QSFP56 HDR transceivers for InfiniBand networking, offering 850nm MMF (up to 100m) and 1310nm SMF (up to 2km) connectivity.

Fluke Networks OptiFiber® Pro High Dynamic Range

Fluke Networks says its OptiFiber Pro High Dynamic Range (HDR) Optical Time Domain Reflectometer is the first to fulfill contractors', installers', and network

High-dynamic-range television

High-dynamic-range television High-dynamic-range television (HDR-TV) is a technology that uses high dynamic range (HDR) to improve the quality of display

MFS1S50-H0xxV 200Gb/s QSFP56 to 2x100Gb/s

Introduction NVIDIA® MFS1S50 is a QSFP56 VCSEL-based (Vertical Cavity Surface-Emitting Laser), cost-effective 200Gb/s to 2 x 100Gb/s active optical

NVIDIA/Mellanox® MMA1T00-HS InfiniBand HDR

The NADDOD Q56-200G-SR4H optical transceiver uses a unique chip to reduce power consumption while utilizing the InfiniBand™ protocol to minimize network

OFP New HDR and v6 Features | Fluke Networks

Our new HDR modules and Version 6.0 software are perfect examples. The new modules plug into any Versiv mainframe to test, troubleshoot and document HDR

100G QSFP28 InfiniBand HDR Mellanox Optical Transceivers

100G IB QSFP28 Transceivers Overview NADDOD 100G InfiniBand EDR modules come in QSFP28 form factor shape, used over single-mode and multi-mode fiber as a media. The product portfolio

How HDR works

Electro-Optical Transfer Function Electro-Optical Transfer Function (EOTF) is one of the core technologies for how HDR works. It's actually a lot less complicated than

NVIDIA/Mellanox Compatible 100G SR2 QSFP56 PAM4

NVIDIA/Mellanox® Compatible 100GBASE-SR2 InfiniBand HPC Optical Transceiver Module (QSFP56, 850nm, OM3/OM4 100m, with FEC, MPO/MTP-12 UPC, DOM,

NVIDIA/Mellanox MMA1T00-HS Compatible 200GBASE

NVIDIA/Mellanox MMA1T00-HS Compatible 200GBASE-SR4 QSFP56 850nm 100m DOM MPO-12/UPC MMF InfiniBand HDR Optical Transceiver Module for

NVIDIA/Mellanox MMA1T00-HS Compatible 200GBASE-SR4

It is qualified for use in InfiniBand HDR end-to-end systems. It is the ideal solution for supercomputing, seamlessly integrating into computing and storage infrastructure to ensure efficient high-performance

InfiniBand 400G/200G HDR | InfiniBand Optical Transceivers and

FS InfiniBand 400G/200G HDR optical modules and cables solution used for high-bandwidth data transmission, data center and AI computing applications. Click to get your 400G/200G HDR optical

200G QSFP56-SR4 850nm 100m MMF InfiniBand HDR Optical

TARLUZ 200G QSFP56 SR4 optic transceiver is designed for 200G Ethernet, it is able to transmit up to 70m via OM3 fiber, and 100m via OM4 fiber. The module with 4x channels, and each channel

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.charratcommunication.fr>

Email: sales@charratcommunication.fr

Phone: +33 1 42 68 93 17

Address: 15 Rue de la Paix, 75002 Paris, France

This document is for informational purposes only. Specifications subject to change without notice.

